

# Container Specifications

<b>INTERNAL DIMENSIONS</b>	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>45' High Cube</b>
Length	19' 4.5"	39' 5.9"	39' 5.9"	44' 5.9"
Width	7' 8.4"	7' 8.4"	7' 8.5"	7' 8.5"
Height	7' 10.1"	7' 10.1"	8' 10.2"	8' 10.2"
Door Opening Width	7' 8.1"	7' 8.1"	7' 8.1"	7' 8.1"
Door Opening Height	7' 5.8"	7' 5.8"	8' 5.8"	8' 5.8"
Cubic Capacity	1165.4 ft	2366.1 ft	2683.9 ft	3040.0 ft
<b>EXTERNAL DIMENSIONS</b>	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>45' High Cube</b>
Length	20'	40'	40'	45'
Width	8'	8'	8'	8'
Height	8' 6"	8' 6"	9' 6"	9' 6"
<b>FLOOR</b>	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>45' High Cube</b>
Floor Type	1.16" wood	1.16" wood	1.16" wood	1.16" wood
Floor Strength Test	16006 lbs*	16006 lbs*	16006 lbs*	16006 lbs*
	<i>*Five passes with ISO compliant test vehicle</i>			
<b>WEIGHT&amp; PAYLOAD</b>	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>45' High Cube</b>
Tare Weight	4916 lbs	8069 lbs	8466 lbs	10470 lbs
Maximum Payload	62281 lbs	63581 lbs	63184 lbs	62330 lbs
Maximum Gross Weight	67197 lbs	71650 lbs	71650 lbs	72800 lbs
<b>Stacking</b>	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>45' High Cube</b>
Stacking Height	8 High	8 High	8 High	8 High
Stacking Test Load per Post	211670 lbs	211670 lbs	211670 lbs	211670 lbs
<b>Cargo Lashing System</b>	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>	<b>45' High Cube</b>
Lashing Rings	8 per side	16 per side	16 per side	16 per side
Lashing Bars	2 per corner	2 per corner	2 per corner	2 per corner

*The dimensions and ratings above are representative of a Container's "typical" specifications. Individual container dimensions, ratings and specification details can vary slightly based on manufacturer, country of origin and other variables*